



Hand protection

NI175

WORKS IN OILY ENVIRONMENT

Popolnoma prevlečena, vodoodporna mehanska rokavica, ki nudi zaščito hrbtne strani dlani



Posebne koristi



Trajnost

· Visokokakovostna prevleka podaljša življenjsko dobo rokavice in zagotavlja odlično zaščito roke



Higiena

· Nitril za uporabnike ne pomeni tveganja za alergije



Uspešnost

· Nitrilna prevleka omogoča ljudem, ki delajo v mastnih/mastnih okoljih, odličen oprijem predmetov, s katerimi ravnavajo.

Certifikati in norme



EN 388
3 1 1 1 X

Aplikacije

- Javna dela
- Stavba
- Avtomobilska
- Rudarska industrija
- Začasno delo
- Javne storitve

Zaščita pred tveganji



Wearing



Hand protection

NI175

WORKS IN OILY ENVIRONMENT

Popolnoma prevlečena, vodoodporna mehanska rokavica, ki nudi zaščito hrbtne strani dlani

Standardi - podrobnosti



EN388:2016+A1:2018

3 [0-4] ODPORNOST PROTI OBRABI

1 [0-5] REZNA UPORNOST

1 [0-4] TEAR RESISTANCE

1 [0-4] PIERCE RESISTANCE

X [A-F] CUT RESISTANCE ISO 13997

Tehnične podrobnosti

Vrsta rokavic	Mehanska rokavica
Družina rokavic	Rezane in šivane rokavice s tekstilno prevleko
Vrsta mehanske rokavice	Odrezano in sešito
Preja za votke	Bombaž
Raven premaza	Popolnoma prevlečen, razen zapestja
Premazni material	Nitril
Finalizacija premaza	s teksturiranim oprijemom
Število plasti	Enoslojni
Material obloge	Bombažni tekstil
Značilnost manšete	Velika varnostna manšeta
Element ugodnosti	Doseganje
Barva	Modra
Velikost	9, 10, 11
Vrsta embalaže	Vrečka v razsutem stanju, 12 kosov

Pakiranje

Prodajna enota: Vrečka v razsutem stanju, 12 kosov
120 pari /box



Safety gloves

NI175

WORKS IN OILY ENVIRONMENT

Fully coated, waterproof, mechanical glove, offering back of hand protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
NI17509	Blue	09	NI175	3295249044008	13295249044005	120	12	15.9 kg	26.6 cm	63.8 cm	39.0 cm
NI17510	Blue	10	NI175	3295249034382	13295249034389	120	12	17.4 kg	26.8 cm	70.6 cm	38.8 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height