Hand protection

KPG10

THERMAL HOT WORKS

Level D cut-resistant ambidextrous thermal glove, combining thermal resistance and finesse, ideal for use in hot environments

Specific benefits

Easy to use

· Perfect fit so that users do not feel any discomfort in the wrist area with prolonged use

Performance

· The high-performance HEATnocut fiber provides resistance to contact heat (250° for 15 seconds)

Compatibility

· Ambidextrous Glove

Certifications and norms

CE CATEGORY II

EN 388
1 X 4 X D

EN 407
4 2 X X X X

Applications

- **Public Works**
- **Building**
- **Finishing Works/Craftsmanship**
- **Maintenance**
- **Automotive**
- **Temporary Work**

Risk Protection

Heat

Cutting

DELTAPLUS

enjoy safety.

Edit 16/10/2026
www.deltaplus-usa.com

Hand protection

KPG10

THERMAL HOT WORKS

Level D cut-resistant ambidextrous thermal glove, combining thermal resistance and finesse, ideal for use in hot environments

Standards - Details

EN388:2016+A1:2018
1 [0-4] ABRASION RESISTANCE
X [0-5] CUT RESISTANCE
4 [0-4] TEAR RESISTANCE
X [0-4] PIERCE RESISTANCE
D [A-F] CUT RESISTANCE ISO 13997

EN 407
THERMAL RISKS (X = NOT TESTED)
4 [0-4] BURNING BEHAVIOUR
2 [0-4] CONTACT HEAT RESISTANCE
X [0-4] CONVECTIVE HEAT
X [0-4] RADIANT HEAT RESISTANCE
X [0-4] SMALL DROP MOLTEN METAL
X [0-4] LARGE QUANTITY MOLTEN METAL

Technical details

Glove kind	Mechanical glove
Glove family	Knitted uncoated glove
Mechanical Glove Type	Tricot
Fiber	Aramid, Cotton
Gauge	7
Benefits element	Para-aramid stitching
Color	Yellow
Size	9
Type of conditioning	Bag of 6

Packaging

Sale unit: Bag of 6
36 pairs /box

Safety gloves

KPG10

THERMAL HOT WORKS

Level D cut-resistant ambidextrous thermal glove, combining thermal resistance and finesse, ideal for use in hot environments

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
KPG1009	Yellow	09	KPG10	3295249035433	13295249035430	36	6	7.5 kg	40.0 cm	32.0 cm	31.0 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height