



Fall protection

LYNX HAR35R

FALL ARRESTER AND SUSPENSION HARNESSES

Technical harness with a new architecture designed to optimise the ergonomics of rope workers



Specific benefits



Comfort

- 3D comfort foam integrated into harness that provides comfort and breathability for prolonged use
- Thermoformed belt provides lumbar support and optimal comfort



Hygiene

- Can wash harnesses and textiles with neutral soap



Performance

- Certification above maximum rated load 100kg: product certified at 150kg



Ease of Use

- Ergonomic design facilitates user movement
- NFC system guarantees traceability

Applications

- Public Works
- Finishing Works/Craftsmanship
- Chemical Industry
- Automotive
- Oil & Gas (Extraction)
- Mining

Certifications and norms



EN361
150 KG

EN813
150 KG

EN358

Risk Protection



Fall



Fall protection

LYNX HAR35R

FALL ARRESTER AND SUSPENSION HARNESSES

Technical harness with a new architecture designed to optimise the ergonomics of rope workers

Standards - Details

Technical details

Type of equipment	Fall arrest, support and suspension harnesses
Composition of the main support	Aluminum, Polyester
Fastening	Buckles
Number of attachment points	2
Number of total suspension points	1
Number of total holding attachment points	2
Anti-fall point	Dorsal, Sternal
Suspension point	Ventral
Holding point	Belt
Color	Grey-Yellow
Comfort elements	"Soft padding" on shoulders and thigh strap, Thermocompressed back and shorts
Size	XS, S/M/L, XL/XXL
Benefits element	Comfort
Number of non-removable buckles	4
Weight (kg)	2,5
Number of manual buckles	2
Number of automatic loops	2
Number of fall arrest anchorage points	2
Padding	Back, Belt, Leg
Sternal	1
Dorsal	1
Belt	1
Fall arrest work situations	Vertical movement on a permanent structure, Work positioning, Movement on lifeline, Restraint, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Vertical movement, confined space,

	than 3 m), Long movement with multi connection /disconnection
--	---



Fall protection

LYNX HAR35R

FALL ARRESTER AND SUSPENSION HARNESSES

Technical harness with a new architecture designed to optimise the ergonomics of rope workers

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
HAR35RGT	Grey-Yellow	M/L	LYNX HAR35R	3295249265304	13295249265301	5	1	14.6 kg	80.0 cm	23.0 cm	32.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height