



Fall protection

AN503180JW

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances



Specific benefits



Hygiene

- Can wash harnesses and textiles with neutral soap



Ease of Use

- NFC system guarantees traceability



Sustainability

- High webbing tenacity thanks to its weave and width

Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Heavy Industry
- Light Industry
- Maintenance

Certifications and norms

ANSI Z359.13-2013 (R2022)



CSA Z259.11-17

Risk Protection



Fall



Fall protection

AN503180JW

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Galvanized steel, Polyester
Length (m)	1.8
With connector	yes
Color	Black-Yellow
Connector 1	Small hook, steel, opening 21 mm
Ending	2 sewn thimble loops
Connectors (structure side)	1 automatic lock hook, steel, opening 65 mm
Lifespan from manufacturing (years)	10
Weight (kg)	1.7
Type of conditioning	Box of 5
Fall arrest work situations	Vertical movement on a permanent structure, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	6



Fall protection

AN503180JW

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN503180JW	Black-Yellow	1,8 m	AN503180JW	3295249219505	13295249219502	5	1	8.9 kg	44.0 cm	28.0 cm	15.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height