



Fall protection

AN208R2AD

ENERGY ABSORBING LANYARDS

Adjustable energy absorbing lanyard allowing the length of the lanyard to be adjusted and therefore reducing the air draft, if necessary



Specific benefits



Hygiene

- Can wash harnesses and textiles with neutral soap



Performance

- Certification above maximum rated load 100kg: product certified at 140kg
- Webbing with better abrasion resistance and certified against sharp edges

Applications

- Public Works
- Finishing Works/Craftsmanship
- Automotive
- Storage

Certifications and norms



EN355

HORIZONTAL CERTIFICATION - 140 KG
RFU 11.062
140 KG

Risk Protection



Fall



Fall protection

AN208R2AD

ENERGY ABSORBING LANYARDS

Adjustable energy absorbing lanyard allowing the length of the lanyard to be adjusted and therefore reducing the air draft, if necessary

Standards - Details

Technical details

Type of equipment	Braided rope lanyard
Composition of the main support	Galvanized steel, Polyester
Length (m)	2
Adjustment	Adjustable by means of a reducing loop on the rope
Rope diameter (mm)	12
With connector	yes
Color	White-Black
Connector 1	Automatic lock hook, steel, opening 19mm
Benefits element	Leading edge
Ending	1 loop sewn thimble
Connectors (structure side)	1 automatic lock hook, steel, opening 55mm
Lifespan from manufacturing (years)	10
Weight (kg)	1,27
Fall arrest work situations	Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	6.5616



Fall protection

AN208R2AD

ENERGY ABSORBING LANYARDS

Adjustable energy absorbing lanyard allowing the length of the lanyard to be adjusted and therefore reducing the air draft, if necessary

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN208R2AD	White-Black	1.50 → 2 m	AN208R2AD	3295249265052	13295249265059	5	1	7.6 kg	18.0 cm	29.4 cm	45.2 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height